

MATCH PRO 15x56 ED

REDEFINING PERFORMANCE AND FEATURE SET EXPECTATIONS

NEW PROPRIETARY ROTATING RETICLE

Offset MRAD based reticle for target sizing, ranging, and follow-up shot correction. The reticle is in the right barrel, has a dedicated focus adjustment and may be rotated for levelling after IPD adjustment.

NEW BRIDGESET - IPD BRIDGE STABILIZER

The user can secure their preferred interpupillary distance to ensure the binocular is set for quick use out of storage and to impart downward pressure onto the binocular for steadying the point-of-aim in windy environments without changing the IPD (folding the bino).

BOTH EYE SPOTTING & KIT CONSOLIDATION

The medium-high magnification power is balanced for long-range spotting with wide FOV. Allows for long-duration spotting without eye-fatigue and takes the place of a spotting scope for most applications therefore reducing overall kit size for the task at hand. The integral reticle expands versatility even further.

SUPERIOR OPTICAL PERFORMANCE

Bak4 Abbe-Koenig roof prisms with perfect internal reflection and PC3 dielectric phase coatings result in over 92% light transmission. ED Prime objective lenses, UWB FMC elements, and EXO-Barrier result in high-resolution imaging regardless of the conditions.

IPX5 INGRESS RATING (WATERPROOF) WITH MAGNESIUM CONSTRUCTION

Rugged magnesium housing ensures the internals are protected during field use and IPX5 rated sealing protects against direct spray beyond what a serious storm could produce. Nitrogen purging for fog-proofing and EXO Barrier coatings applied to exterior surfaces for exceptional protection against contaminants and image distorting water buildup.

CONVENIENT LAYOUT AND DESIGN

Smooth center focus-wheel, locking primary image calibration diopter, fine-control reticle focusing diopter, and reticle rotation ring all allow the binocular to be calibrated to the user's vision.

BACKED BY THE LIFETIME IRONCLAD WARRANTY


The Match Pro 15x56 ED binocular is backed by a 20-year lifetime warranty and is engineered and manufactured to withstand the rigors of the outdoors. The materials and workmanship are covered for 20 years from date of purchase or manufacturing date. Fully transferable, no receipt required. Full details at [Bushnell.com/warranty](https://bushnell.com/warranty).

PURPOSE-BUILT FOR:

Users who demand a bright, clear binocular with high-magnification and a reticle for training, range estimation or target sizing, and follow-up shot correction.

IDEAL FOR:

- Competition
- Training/Target Shooting
- Professional Use
- Long-Range Hunting/Spotting



SHOT-CALL MRAD RETICLE
RIGHT BARREL LEVELING



BRIDGESET
IPD STABILIZER



BRIDGESET - FORWARD POSITION



20 YEARS
CHASSIS & OPTICS



SKU	RETICLE	RETICLE SYSTEM	EXIT PUPIL (mm)	FOCUS RANGE (ft)	FIELD OF VIEW (X) ft@1000yds m@1000m	INGRESS RATING	LENGTH (in)	WEIGHT (oz)
BMP1556G	SHOTCALL	MRAD BASED	3.8	13 to Infinity	236 78.7	IPX5	8.6	52