

Bushnell®



SCAN ME

SCAN THE QR CODE FOR THE FULL INSTRUCTION
MANUAL ON THE MATCH PRO ED BINOCULAR



MATCH PRO

WWW.BUSHNELL.COM



**MATCH PRO ED
SPOTTING BINOCULAR
QUICK START GUIDE**

REV A

MATCH PRO ED BINOCULAR SETUP STEPS

(Note: Due to the high magnification, a tripod and mounting adapter or other suitable support is useful for steadying target images during this process)

1. For all steps, it is best to leave both eyes open. Closing one eye can affect the focus of the other.

Adjust interpupillary distance to your eye spacing and Twist-Up Eyecup position until the full field of view is visible.



2. While looking at a light-colored blank wall or similar plain background, use the Main Focus knob to make the background out-of-focus. Concentrate on the right-barrel reticle and rotate the Reticle Focus Diopter ring in either direction until it is sharp. Cover the Left Objective Lens with attached lens cap, if needed.



3. Cover the Left Objective Lens with the attached lens cap and observe a target image with fine details such as a distant sign or label with printed words. Use the Main Focus knob for adjustment until the target image is sharp.



4. **DO NOT ADJUST THE MAIN FOCUS KNOB DURING THIS STEP.**

Next cover the Right Objective Lens and uncover the Left. Unlock the left Image Calibration Diopter by pulling the ring towards the eyecup. Observe the same target image as in Step 3 and calibrate the left-barrel focus by rotating the diopter in either direction. When finished, lock the diopter ring back into place by pushing it towards the objective lens.



5. Focus on a target image and level the reticle with the horizon using the Reticle Leveling control ring. This control ring does not lock, but is relatively stiff to turn to reduce accidental adjustment.

With both objective lenses uncovered, use the binocular normally and observe a target image only adjusting the Main Focus knob. If the target image in either eye and/or reticle is not sharp, repeat steps #2 thru #4. Any adjustments to either Diopter should be minor as compared to the 1st pass.



The binocular is now calibrated to your vision, and the Main Focus knob is typically all you'll need to adjust moving forward.

6. If desired, install the BridgeSet IPD Stabilizer into one of the 2 accessory lug locations by first removing the related protective cap, and then use the forward thumb-screw to attach. The included hex key may be used to tighten further, but do not overtighten. Finally, expand the stabilizer legs by rotating the upper thumb-screw until the legs contact the bottoms of both barrels.

